



FREQUENCY (HZ)		100	125	160	200	250	315	400	500	630	800	1000	1250	1600	2000	2500	3150	4000	5000
SOUND ABSORPTION VALUES	Without Mineral Wool	0,41	0,48	0,44	0,51	0,56	0,59	0,61	0,67	0,65	0,62	0,64	0,70	0,75	0,80	0,89	0,96	1,01	1,01
	With Mineral Wool	0,56	0,57	0,49	0,55	0,58	0,60	0,61	0,66	0,67	0,69	0,70	0,70	0,73	0,81	0,90	0,99	1,00	0,95

GENERAL FEATURES

Materials	MDF Standart D-s2.d0 MDF FR B-s2.d0 Plasmen Fabric
Thickness (mm)	18mm
Weight (Approximately)	9,50 kg/m2 18mm Standart MDF 11,50 kg/m2 18mm Fire Resistant MDF
Application	French Cleat

ACOUSTIC VALUES

Mounting Depth 200mm	NRC	Euro Class
Without Mineral Wool	0,65	C
With Mineral Wool	0,70	C
Mineral Wool	50 mm	50 kg/m3

Sizes

Standart MDF	Fire Resistant MDF
580x900	600x600
580x1800	600x1200
600x1200	600x2400

Absorption according to EN ISO 354

