

PERFOPAN Akustik Panelleri – Ses Yutma TablosuAna Firma: ISUS 1932 Ltd Şti - Web : www.perfopan.com Email : info@perfopan.com

Ürün Adı	Delikli Panel Kodları	Perforasyon Oranı	Taş Yünü	Hava Boşluğu	NRC	aw	Euro Class	125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz	5000Hz
Perfofire	PF 32x32x8mm DS 1000	5 %	50mm	200mm	0.35	0.35	D	0.39	0.39	0.40	0.35	0.23	0.14	0.20
	PF 32x32x8mm DS 2000	13 %	None	200mm	0.60	0.60	D	0.42	0.60	0.71	0.52	0.42	0.46	0.40
	PF 32x32x8mm DS 2000	13 %	50mm	200mm	0.60	0.60	C	0.52	0.58	0.65	0.63	0.52	0.47	0.48
	PF 16x16x8mm DS 4000	20 %	None	200mm	0.75	0.75	C	0.41	0.74	0.89	0.64	0.63	0.65	0.65
	PF 16x16x8mm DS 4000	20 %	50mm	200mm	0.80	0.85	B	0.61	0.78	0.87	0.83	0.77	0.73	0.72
	PF 16x16x8mm DS 3000	16 %	50mm	200mm	0.70	0.70	C	0.52	0.77	0.78	0.67	0.56	0.47	0.54
	PF 16x16x3mm DS 8000	6 %	50mm	200mm	0.40	0.40	B	0.42	0.44	0.46	0.40	0.28	0.19	0.22
	PF 16x16x6mm DS 8000	23 %	50mm	200mm	0.80	0.80	C	0.51	0.81	0.90	0.75	0.72	0.66	0.72
	PF 8x8x2mm DS 16000	5 %	50mm	200mm	0.40	0.40	D	0.44	0.45	0.46	0.39	0.26	0.18	0.21

Ürün Adı	Derzli Panel Kodları	Perforasyon Oranı	Taş Yünü	Hava Boşluğu	NRC	aw	Euro Class	125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz	5000Hz
Perfofire	2S 6A DS 4000	8 %	50mm	200mm	0.85	0.83	B	0.48	0.87	0.93	0.79	0.75	0.71	0.68
	2S 14A DS 4000	8 %	50mm	200mm	0.80	0.80	C	0.54	0.85	0.90	0.77	0.69	0.64	0.58
	2S 30A DS 2000	4 %	50mm	200mm	0.60	0.55	D	0.53	0.74	0.74	0.59	0.43	0.39	0.42
	3S 5A DS 4000	13 %	50mm	200mm	0.85	0.85	B	0.48	0.86	0.93	0.79	0.76	0.72	0.73
	3S 13A DS 4000	13 %	50mm	200mm	0.85	0.85	B	0.52	0.79	0.94	0.79	0.77	0.77	0.79
	4S 12 A DS 4000	16 %	50mm	200mm	0.85	0.85	B	0.51	0.83	0.94	0.79	0.78	0.71	0.74
	4S 28A DS 2000	6 %	50mm	200mm	0.55	0.50	D	0.48	0.61	0.65	0.54	0.40	0.25	0.31
	4S 64A DS 1000	5 %	50mm	200mm	0.45	0.45	D	0.45	0.54	0.52	0.41	0.26	0.29	0.35
	SLT 7x7 SS 300	12 %	50mm	200mm	0.60	0.60	D	0.48	0.65	0.68	0.58	0.45	0.33	0.35
	SLT 7x7 SS 600	29 %	50mm	200mm	0.80	0.80	B	0.46	0.85	0.91	0.77	0.74	0.64	0.65